

HS-150 Premium Accelerometer


AC acceleration output via PUR Cable

Key Features

- Waterproof
- Resistant to oil
- Premium design

Industries

Building services, Pulp and Paper,
Mining, Metals, Utilities, Automotive,
Water, Pharmaceutical



Technical Performance

Mounted Base Resonance	see: 'How To Order' table (nominal)
Sensitivity	see: 'How To Order' table $\pm 10\%$ Nominal 80Hz at 22°C
Frequency Response	1.5Hz (90cpm) to 10kHz (600kcpm) $\pm 5\%$ 0.5Hz (30cpm) to 12kHz (720kcpm) $\pm 10\%$ 0.2Hz (12cpm) to 15kHz (900kcpm) $\pm 3\text{dB}$
Isolation	Base isolated
Range	see: 'How To Order' table
Transverse Sensitivity	Less than 5%

Mechanical

Case Material	Stainless Steel
Sensing Element/Construction	PZT/Shear
Mounting Torque	8Nm
Weight	140gms (nominal)
Maximum Cable Length	1000 metres
Standard Cable Length	5 metres
Screened Cable	PUR - length to be specified with order
Mounting Threads	see: 'How To Order' table
Submersible Depth	100 metres max (10 bar)


Electrical

Electrical Noise	0.1mg max
Current Range	0.5mA to 8mA
Bias Voltage	10 - 12 Volts DC
Settling Time	1 second
Output Impedance	200 Ohms max.
Case Isolation	$>10^8$ Ohms at 500 Volts

Environmental

Operating Temperature Range	-30 to 90°C
Sealing	IP68
Maximum Shock	5000g
EMC	EN61326-1:2013


Typical Frequency Response (at 100mV/g)



Applications

Fans, Motors, Pumps, Compressors,
Centrifuges, Conveyors, Air Handlers,
Gearboxes, Rolls, Dryers, Presses,
Cooling, VAC, Spindles, Machine Tooling,
Process Equipment

Vibration sensor should be firmly fixed to a flat surface
(spot face surface may be needed to be produced and
cable anchored to sensor body.)



How To Order

Product Prefix HS - Hansford Sensors		Product Series 150 - Premium Industrial Vibration Sensor					Cable Length (if integral cable) QXX - length specified in metres							
H	S	1	5	0	X	X	X	X	X	X	X	X	X	X
Extra Options (if required)		Sensitivity		Range		Resonant Frequency		Cable/Connector		Mounting Threads				
F - Filtered		010 - 10mV/g		$\pm 800\text{g}$		28kHz (1,680kcpm)		01 - PUR		01 - 1/4-28" UNF Female				
L - 316L Stainless Steel		030 - 30mV/g		$\pm 250\text{g}$		26kHz (1,560kcpm)		02 - Braided		02 - 1/4-28" UNF Male				
RT - Temperature Output PT100		050 - 50mV/g		$\pm 160\text{g}$		24kHz (1,440kcpm)		07 - Silicon		05 - Quick Fit Female				
S - 90° Side Exit		100 - 100mV/g		$\pm 80\text{g}$		22kHz (1,320kcpm)		08 - Flame Retardant		06 - M6 x 1mm Male				
T - Temperature Output		250 - 250mV/g		$\pm 32\text{g}$		20kHz (1,200kcpm)		50 - 2 Pin MS		08 - M8 x 1.25mm Male				
Y - 5% tolerance on sensitivity		500 - 500mV/g		$\pm 16\text{g}$		18kHz (1,080kcpm)		54 - M12		10 - M10 x 1.5mm Male				



www.hansfordsensors.com
sales@hansfordsensors.com

We reserve the right to alter the specification of this product without prior notice

TS278.5

